

# STONE SPECIFIC® STONE ENHANCER & SEALER

- Protects and color-enhances marble, stone and grout
- Penetrating sealer resists dirt and stains
- Enriches the color and texture of stone
- 20 Year Satisfaction Guarantee



PRICE



## PRODUCT DESCRIPTION

Color enhancer and penetrating sealer for all types of porous natural stone and grout. Rejuvenates the color and appearance of worn, faded stone, tumbled marble and other rustic-look stones. Can also be used to darken the color of grout. Provides long-lasting protection against oil, grease and stains. Its water-based, low odor formula can be used indoors or outdoors.

StoneSpecific® No VOC (Volatile Organic Compound) formulas help provide better indoor and outdoor air quality compared to similar traditional products.

## USES

As a sealer and color enhancer for all stone surfaces, clay pavers and grout. Excellent for tumbled marble and other rustic look stones. This product may not be totally effective as a color enhancer on some polished stones. For interior and exterior use.

## SURFACE PREPARATION

Surface should be dry, clean and free of waxes, sealers or finishes. TileLab® Heavy-Duty Cleaner & Stripper will clean the surface or strip wax and acrylic finishes. New installations need to be cured 48 hours before application. Once the enhancer has been applied to the surface of stone, grout or tile it cannot be reversed. Always test product in hidden area to ensure desired results.

## APPLICATION

Apply liberally using a new mop, lambswool applicator or sponge. Allow to penetrate for up to 5 minutes. Immediately wipe off any sealer completely before it dries. Immediately apply a second coat. Ensure no residue is left to dry on the surface. Surface of stone should be maintained at a temperature above 50° F (10° C) or below 100° F (38° C) until sealer cures. Do not use outside if inclement weather is expected within 24 hours. Clean off any residue left on the surface with an appropriate StoneSpecific® or TileLab® cleaner.

Note: The more porous the stone the deeper the color enhancement.

## DRYING TIME

4 - 6 hours. Do not clean for 24 hours.

## COVERAGE

### On Porous Surfaces:

43 – 85 sq. ft. per quart (4.2 – 8.3 M<sup>2</sup> per 946 ml).

### On Polished or Dense Surfaces:

170 – 255 sq. ft. per quart (16.6 – 25 M<sup>2</sup> per 946 ml).

## CLEAN-UP

Clean tools and hands with soap and water immediately after use.



**CUSTOM®**  
BUILDING PRODUCTS

## SAFETY

MAY BE HARMFUL IF SWALLOWED. MAY IRRITATE EYES AND SKIN. Wear skin and eye protection. Contains Ethylene Glycol, Dibutyl phthalate, Dipropylene glycol methyl ether and acrylic polymer. If in eyes, flush with water for at least 15 minutes. If on skin, wash with soap and water. If irritation persists, seek medical attention. If swallowed, DO NOT induce vomiting. Seek medical attention. KEEP OUT OF REACH OF CHILDREN.

## ORDERING INFORMATION

	ITEM CODE	SIZE	PACKAGE
USA	SSSESQT-3	1 quart (946 ml)	Bottle
Canada	CSSSESQT-3	1 quart (946 ml)	Bottle

## LIMITED WARRANTY

Custom Building Products ("Custom") warrants to the original consumer purchaser that its product shall be free from defects in material and workmanship under normal and proper usage for a period of one year following the date of original purchase. Custom's sole liability under this warranty shall be limited to the replacement of the product. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty will not extend to any product which has been modified in any way or which has not been used in accordance with Custom's printed instructions. Custom makes no other warranties either express or implied. This warranty gives you specific legal rights, and you may have other rights that vary from state to state.

