

MATERIAL SAFETY DATA SHEET

CrackBuster Pro

HMIS

HEALTH	1
FLAMMABILITY	0
REACTIVITY	0
PERSONAL PROTECTION	B

1. Product And Company Identification

Supplier

CUSTOM BUILDING PRODUCTS
 10400 Pioneer Blvd., Unit #3
 Santa Fe Springs, CA 90670 UNITED STATES

Company Contact: GEORGE MARCINA
Telephone Number: (562) 968-2980 Ext 103
FAX Number: (562) 903-2697
E-Mail: georgem@cbpmail.net
Web Site: www.custombuildingproducts.com

Manufacturer

CUSTOM BUILDING PRODUCTS
 10400 Pioneer Blvd., Unit #3
 Santa Fe Springs, CA 90670 UNITED STATES

Company Contact: GEORGE MARCINA
Telephone Number: (562) 968-2980 Ext 103
FAX Number: (562) 903-2697
E-Mail: georgem@cbpmail.net
Web Site: www.custombuildingproducts.com

Supplier Emergency Contacts & Phone Number

GEORGE MARCINA: (562) 968-2980

Manufacturer Emergency Contacts & Phone Number

GEORGE MARCINA: (562) 968-2980

Issue Date: 03/16/2007

Product Name: CrackBuster Pro
Chemical Name: Rubber Modified Asphalt
CAS Number: Not Established
Chemical Family: Asphalt
Chemical Formula: Mixture
MSDS Number: 800
Product Code: PolyG

2. Composition/Information On Ingredients

Ingredient Name	CAS Number	Percent Of Total Weight
AluminumFoil	Not establish	0 - 2
Bitumen, Cracking Residue	8052-42-4	65 - 84
Calcium Carbonate	471-34-1	0 - 15
Nylon as fabric or film	Not Establish	0 - 5
Petroleum Hydrocarbon Resin	68527-25-3	0 - 8
Polyester as fabric or film	Not establish	0 - 8
Polyethylene as fabric or film	9002-88-4	0 - 8
Polypropylene as fabric or film	9003-07-0	0 - 8
Proprietary Ingredient	Not Establish	0 - 5
Styrene - Butadiene	9003-55-8	0 - 15
Talc	14807-96-6	0 - 15

MATERIAL SAFETY DATA SHEET

CrackBuster Pro

3. Hazards Identification

Primary Routes(s) Of Entry

Skin and Inhalation

Eye Hazards

Not likely. Mechanical irritation.

Skin Hazards

Slight irritation

Ingestion Hazards

Not likely.

Inhalation Hazards

Inhalation could occur if product is heated to molten state.

Chronic/Carcinogenicity Effects

Contains ingredients listed by IARC as Group 3 - Not classifiable as to carcinogenic or non carcinogenic to humans.

4. First Aid Measures

Eye

In case of contact, hold eyelids apart and immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately.

Skin

In case of irritation wash thoroughly with water and soap. If irritation persist, get medical attention.

Ingestion

If there is any discomfort from ingestion, consult a physician.

Inhalation

Remove to fresh air. Consult a physician immediately if irritation persists.

5. Fire Fighting Measures

Flash Point: >525 °F

Flash Point Method: COC

Lower Explosive Limit: N/A

Upper Explosive Limit: N/A

Extinguishing Media

Water, Foam, CO2

Fire Fighting Instructions

Wear self-contained breathing apparatus

6. Accidental Release Measures

No Data Available...

7. Handling And Storage

Handling And Storage Precautions

Store in dry, ventilated areas, away from heat. Do not store in temperatures above 200 F

Work/Hygienic Practices

Maintain good personal hygiene and housekeeping practices.

8. Exposure Controls/Personal Protection

No Data Available...

MATERIAL SAFETY DATA SHEET

CrackBuster Pro

8. Exposure Controls/Personal Protection - Continued

Eye/Face Protection

Protect from mechanical intrusion.

Skin Protection

Use impervious gloves.

Respiratory Protection

Local exhaust is usually satisfactory.

Ingredient(s) - Exposure Limits

Bitumen, Cracking Residue

NIOSH - PEL - 5mg/m³ - fumes

ACGIH - TLV - 5 mg/m³ - fumes

Calcium Carbonate

ACGIH TLV-TWA 10 mg/m³

OSHA PEL-TWA 15 mg/m³

OSHA PEL-TWA 5 mg/m³

Talc

ACGIH TLV-TWA 2 mg/m³

OSHA PEL-TWA 20 mppcf

9. Physical And Chemical Properties

Appearance

Sheet like material, in rolls.

Odor

Possible slight odor.

Chemical Type: Mixture

Physical State: Solid

Melting Point: > 200 °F

Boiling Point: N/A °F

Specific Gravity: 1.0 - 1.3

Percent VOCs: 0 g/l

Vapor Density: N/A

Solubility: NONE

Evaporation Rate: N/A

10. Stability And Reactivity

Stability: STABLE

Hazardous Polymerization: WILL NOT OCCUR.

Conditions To Avoid (Stability)

High temperature will cause material to melt.

Hazardous Decomposition Products

C0, CO₂, Smoke,

11. Toxicological Information

Chronic/Carcinogenicity

Contains ingredients listed by IARC as Group 3 - Not classifiable as to carcinogenic or non carcinogenic to humans.

Ingredient(s) - Carcinogenicity

Bitumen, Cracking Residue

Listed In The IARC Monographs

Nylon as fabric or film

MATERIAL SAFETY DATA SHEET

CrackBuster Pro

11. Toxicological Information - Continued

Ingredient(s) - Carcinogenicity - Continued

Listed In The IARC Monographs

Polyester as fabric or film

Listed In The IARC Monographs

Polyethylene as fabric or film

Listed In The IARC Monographs

Polypropylene as fabric or film

Listed In The IARC Monographs

Styrene - Butadiene

Listed In The IARC Monographs

Talc

Listed In The IARC Monographs

Bitumen, Styrene-butadiene, Talc, Polyethylene, Polypropylene, Polyester and Nylon were evaluated by IARC and are listed as Group 3 - Not classifiable as to carcinogenic or non carcinogenic to humans.

12. Ecological Information

No Data Available...

13. Disposal Considerations

Dispose in accordance with State, Local and Federal regulations.

RCRA Information

Not considered RCRA waste.

14. Transport Information

DOT Shipping Label

NOT REGULATED

15. Regulatory Information

Ingredient(s) - State Regulations

Calcium Carbonate

Pennsylvania - Workplace Hazard

Styrene - Butadiene

California - Proposition 65

Talc

New Jersey - Workplace Hazard

Pennsylvania - Workplace Hazard

Massachusetts - Hazardous Substance

16. Other Information

HMIS Rating

Health: 1

Fire: 0

Reactivity: 0

Personal Protection: B

Revision/Preparer Information

MSDS Preparer: GEORGE MARCINA

MSDS Preparer Phone Number: (323) 582-0846

This MSDS Supersedes A Previous MSDS Dated: 10/15/2002

MATERIAL SAFETY DATA SHEET

CrackBuster Pro

Disclaimer

THE INFORMATION PRESENTED HERE IS BELIEVED TO BE ACCURAE BUT IS NOT WARRANTED TO BE, WHETHER ORIGINATING WITH THE COMPANY OR NOT. RECIPIENTS ARE ADVISED TO CONFIRM IN ADVANCE OF NEED, THAT THE INFORMATION IS CURRENT, APPLICABLE, AND SUITABLE TO THEIR CIRCUMSTANCES.

CUSTOM BUILDING PRODUCTS

Printed Using MSDS Generator™ 2000