GTS Sanded Thin-Set, Grey and White

HMIS		
HEALTH 1		
FLAMMABILITY 0		
REACTIVITY 0		
PERSONAL PROTECTION E		
1. Product And Company Identification		
<u>Supplier</u> JAMO 8850 NW 79 AVE. MIAMI, FL 33166 USA	<u>Manufacturer</u> CUSTOM BUILDING PRODUCTS 10400 Pioneer Blvd., Unit #3 Santa Fe Springs, CA 90670 UNITED STATES	
Company Contact: GEORGE MARCINA Telephone Number: (562)968-2980 ex 103 FAX Number: (562)903-2697 E-Mail: georgem@cbpmail.net Web Site: JAMOINC.COM	Company Contact: GEORGE MARCINA Telephone Number: (562) 968-2980 Ext 103 FAX Number: (562) 903-2697 E-Mail: georgem@cbpmail.net Web Site: www.custombuildingproducts.com	
<u>Supplier Emergency Contacts & Phone Number</u> George Marcina: (562) 968-2980 ext 103	Manufacturer Emergency Contacts & Phone Number GEORGE MARCINA: (562) 968-2980	
Chemical Name: Mortars CAS Number: Not Established Chemical Family: Mixture Chemical Formula: Mixture MSDS Number: 765 Product Code: 6401		
2. Composition/Information On Ingredients		
Ingredient Name	CAS Number	Percent Of Total Weight
PortlandCement	65997-15-1	35 - 45
SILICA, Quartz, Crystaline	14808-60-7	55 - 60
3. Hazards Identification Primary Routes(s) Of Entry Inhalation, Skin Contact, Eye Contact, Ingestion Eye Hazards		
Irritant, severe eye irritation. May cause eye injury. Effect	s may be delayed.	
Skin Hazards Contains Portland cement and exposure to dry Portland c irritation. Prolonged contact with wet Portland cement may cause s form of chemical (caustic) burns.	. , , ,	
Ingestion Hazards Ingestion is not known to be harmful, however the product	contains Portland cement which is caust	ic to mucus

GTS Sanded Thin-Set, Grey and White

3. Hazards Identification - Continued

Ingestion Hazards - Continued

tissue and should not be consumed.

Inhalation Hazards

Causes respiratory tract irritation. May cause nose, throat, and lung irritation. May cause delayed lung injury.

Chronic/Carcinogenicity Effects

Contains Silica sand, known Human Carcinogen (Category 1)

4. First Aid Measures

<u>Eye</u>

In case of contact, hold eyelids apart and immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately if irritation develops and persists.

<u>Skin</u>

In case of contact, immediately flush skin with plenty of water for at least 15 minutes. Get medical attention immediately if irritation (redness, rash, blistering) develops and persists.

Ingestion

DO NOT INDUCE VOMITING. If victim is fully conscious, give one or two cups of water or milk to drink. Get medical attention immediately.

Inhalation

If inhaled, remove to fresh air. Consult a physician immediately if irritation persists. Do not give an unconscious person anything to drink.

5. Fire Fighting Measures

Flash Point: N/A °F Flash Point Method: N/A Lower Explosive Limit: N/A Upper Explosive Limit: N/A

6. Accidental Release Measures

Avoid generating dust. Sweep up and remove immediately.U se appropriate personal protective equipment (PPE). OBSERVE ALL FEDERAL, STATE AND LOCAL REGULATIONS REGARDING NOTIFICATIONS OF ACCIDENTAL RELEASES.

7. Handling And Storage

Handling And Storage Precautions

Use only with adequate ventilation.

Handling Precautions

Avoid creating dust. Avoid breathing dust. Avoid contact with skin and clothing. Avoid contact with eyes.

Storage Precautions

Keep dry until ready to use.

Work/Hygienic Practices

Use good personal hygiene. Wash thoroughly with soap and water after handling.

8. Exposure Controls/Personal Protection

Engineering Controls

Use with adequate ventilation.

GTS Sanded Thin-Set, Grey and White

. Exposure Controls/Personal Protection - Continued
ye/Face Protection Safety glasses with side shields or goggles recommended.
ikin Protection If hands or feet will be exposed, wear impervious gloves and/or boots.
espiratory Protection In case of inadequate ventilation and when exposed to dust above the recommended limits, wear a suitable NIOSH-approved respirator.
ngredient(s) - Exposure Limits Portland Cement OSHA - PEL - 5mg/m3 OSHA - PEL - TWA - 50mppcf ACGIH - TLV - 10mg/m3 SILICA, Quartz, Crystaline ACGIH TLV-TWA 0.05 mg/m3 OSHA PEL-TWA 30/%SiO2+2mg/m3 OSHA PEL - TWA 10/% SiO2 +2 mg/m3 OSHA PEL-TWA 250/%SiO+5 mppcf Cal EPA - OEHHA - REL - 3 micrograms/m3
. Physical And Chemical Properties
ppearance Free flowing white or gray powder.
Chemical Type: Mixture Physical State: Solid Colling Point: N/A °F Capecific Gravity: 2.7 Capor Density: N/A Colubility: SLIGHT Couporation Rate: N/A
0. Stability And Reactivity
tability: STABLE
lazardous Polymerization: WILL NOT OCCUR.

Conditions To Avoid (Stability)

Avoid unintentional contact with water.

Incompatible Materials

Contains portland cement which, when wet, is highly alkali. As a result, it is incompatible with acids, ammonium salts, aluminum and other alkali and alkaline earth metals.

11. Toxicological Information

Chronic/Carcinogenicity

Contains Silica sand, known Human Carcinogen (Category 1)

Ingredient(s) - Carcinogenicity

SILICA, Quartz, Crystaline NTP - Listed On The National Toxicology Program Listed In The IARC Monographs

GTS Sanded Thin-Set, Grey and White

12. Ecological Information

No Data Available...

13. Disposal Considerations

Dispose in accordance with applicable federal, state and local government regulations.

RCRA Information

Not considered RCRA Hazardous Waste.

14. Transport Information

DOT Shipping Label

NOT REGULATED

15. Regulatory Information

SARA Hazard Classes

Chronic Health Hazard

SARA Section 313 Notification

This product does not contains toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 and of 40 CFR 372.

Ingredient(s) - U.S. Regulatory Information

SILICA, Quartz, Crystaline SARA Title III - Section 313 Form "R"/TRI Reportable Chemical SARA - Chronic Health Hazard

State Regulations

Cal EPA -Toxic Hot Spots - OEHHA - REL - 3 micrograms /m3

Ingredient(s) - State Regulations

Portland Cement New Jersey - Workplace Hazard Pennsylvania - Workplace Hazard SILICA, Quartz, Crystaline New Jersey - Workplace Hazard Pennsylvania - Workplace Hazard California - Proposition 65 Massachusetts - Hazardous Substance

16. Other Information

HMIS Rating Health: 1 Fire: 0 Reactivity: 0 Personal Protection: E

Revision/Preparer Information MSDS Preparer: GEORGE MARCINA **MSDS Preparer Phone Number:** (562) 968-2980 ext 103 **This MSDS Supersedes A Previous MSDS Dated:** 11/07/2006

Disclaimer

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained therein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of

GTS Sanded Thin-Set, Grey and White

Disclaimer - Continued

its use. Each individual should make a determination as to the suitability of the information for their particular purposes(s).

JAMO

Printed Using MSDS Generator[™] 2000