

# **Section 1: IDENTIFICATION**

#### 1.1 PRODUCT IDENTIFIER

Product Name: Wall Mud Pre-Mixed Lightweight Browncoat

Product Code: Not Available

1.2 RECOMMENDED USE OF CHEMICAL AND RESTRICTIONS ON USE

Product Use: Bedding Mortar.

1.3 DETAILS OF THE SUPPLIER OF THE SAFETY DATA SHEETS

Name/Address: Jamo

3490 Piedmont Road, Suite 1300

Atlanta, GA 30329

**Telephone Number:** (562)-598-8808

#### 1.4 EMERGENCY TELEPHONE NUMBER

**Emergency Telephone** INFOTRAC 1-800-535-5053 (US and Canada)

Number: INTERNATIONAL + 1-352-323-3500

# Section 2: HAZARD(S) IDENTIFICATION

### 2.1 CLASSIFICATION OF THE CHEMICAL IN ACCORDANCE WITH PARAGRAPH (d) OF 29 CFR

1910.1200 (OSHA HAZCOM2012)

Skin IrritationCategory 2Serious Eye DamageCategory 1STOT-SECategory 3STOT-RECategory 1CarcinogenicityCategory 1A

#### 2.2 LABEL ELEMENTS ACCORDING TO OSHA HAZCOM2012

### 2.2a SIGNAL WORD:

DANGER!

# 2.2b HAZARD STATEMENTS

Causes skin irritation

Causes serious eye damage May cause respiratory irritation

Causes damage to organs through prolonged or repeated exposure

May cause cancer



### 2.2c HAZARD PICTOGRAMS



### 2.2d PRECAUTIONARY STATEMENTS

| i.   | PREVENTION | Wash hands thoroughly after handling. Do not breathe dust/fume/gas/mist/ vapors/spray. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection.   |
|------|------------|---|
| ii.  | RESPONSE   | If on skin: Wash with plenty of water. Take off contaminated clothing and wash it before reuse. If skin irritation or rash occurs: Get medical advice/attention. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If inhaled: Remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: call a poison center/doctor. If exposed or concerned: get medical advice/attention |
| iii. | STORAGE    | Store in a well-ventilated place. Keep container tightly closed.  |
| iv.  | DISPOSAL   | Dispose of contents/containers in accordance with all local, state, provincial, and federal regulations.  |

# 2.3 ADDITIONAL INFORMATION

# 2.3a HNOC – HAZARDS NOT OTHERWISE CLASSIFIED

Not applicable

# 2.3b UNKNOWN ACUTE TOXICITY

98% of the mixture consists of ingredient(s) of unknown acute toxicity.

# 2.3c WHMIS CLASSIFICATION

Class D2B – Skin/Eye Irritant Class D2A – Chronic Toxic Effects

Class D2A - Carcinogenicity Class E – Corrosive Material

## 2.3d LABEL ELEMENTS ACCORDING TO WHMIS

# i. WHMIS HAZARD SYMBOLS





Page 2 of 12



# ii. SIGNAL WORD DANGER!

# Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

# 3.1 MIXTURES

| Chemical Name              | CAS Number | Weight % |
|----------------------------|------------|----------|
| Portland Cement            | 65997-15-1 | 30 – 60% |
| Crystalline Silica, Quartz | 14808-60-7 | 10 – 30% |
| Calcium Hydroxide          | 1305-62-0  | 10 – 30% |
| Gypsum                     | 7778-18-9  | 1 – 5%   |

# **Section 4: FIRST-AID MEASURES**

# 4.1 DESCRIPTION OF THE FIRST-AID MEASURES

| ROUTES OF EXPOSURE | DESCRIPTION  |
|--------------------|--|
| Eye Contact:       | In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. If easy to do, remove contact lenses, if worn. Get medical attention immediately.                       |
| Skin Contact:      | In case of contact, immediately flush skin with plenty of water.<br>Remove contaminated clothing and shoes. Wash clothing before<br>reuse. Call a physician if irritation develops and persists. |
| Inhalation:        | If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell.                                 |
| Ingestion:         | If swallowed, do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical advice/attention.                         |

# 4.2 MOST IMPORTANT SYMPTOMS/EFFECTS, ACUTE AND DELAYED

| ROUTES OF EXPOSURE | DESCRIPTION   |
|--------------------|---|
| Eye Contact:       | Causes serious eye damage. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva. |
| Skin Contact:      | Causes skin irritation. Handling can cause dry skin, discomfort, irritation, and dermatitis.  |
| Inhalation:        | May cause respiratory tract irritation. Causes damage to organs through prolonged or repeated exposure. This product contains                                 |

Page 3 of 12



crystalline silica. Prolonged or repeated inhalation of respirable crystalline silica from this product can cause silicosis, a serious disabling and fatal lung disease.

Ingestion: May be harmful if swallowed. Ingestion may cause discomfort

and/or distress, nausea or vomiting.

### 4.3 INDICATION OF IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED

Not applicable

# **Section 5: FIRE-FIGHTING MEASURES**

#### **5.1 FLAMMABILITY**

Flammability: Not Flammable by WHMIS/OSHA HAZCOM2012 Criteria

#### **5.2 EXTINGUISHING MEDIA**

# 5.2a. Suitable Extinguishing Media:

Treat for surrounding material.

# 5.2b. Unsuitable Extinguishing Media:

Not available.

# 5.3 SPECIFIC HAZARDS ARISING FROM THE CHEMICAL

### 5.3a. Products of Combustion:

May include, and are not limited to: oxides of carbon and hydrogen sulfide

# 5.3b. Explosion Data

i. Sensitivity to Mechanical Impact:

Not available.

ii. Sensitivity to Static Discharge:

Not available.

# Section 6: ACCIDENTAL RELEASE MEASURES

# 6.1 PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT, AND EMERGENCY PROCEDURES

Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.

# 6.2 METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING UP

Methods for Containment: Recover all usable material. Pick up large pieces, and then place in

a suitable container. Do not flush to sewer or allow to enter



waterways. Use appropriate Personal Protective Equipment (PPE).

**Methods for Cleaning-Up:** Vacuum or sweep material and place in a disposal container.

Dispose of unwanted material properly in accordance with all local,

regional, national and international regulations.

# Section 7: HANDLING AND STORAGE

#### 7.1 PRECAUTIONS FOR SAFE HANDLING

Handling: Use in well-ventilated areas. Wear chemical resistant gloves and

eye protection. Do not mix with other chemical products, except as indicated by the manufacturers. Do not get in eyes. Do not get on skin or clothing. Do not breathe fumes. Do not take internally. Good

housekeeping is important to prevent accumulation of dust.

General Hygiene Advice: Use good industrial hygiene practices and wear recommended

personal protection. Launder contaminated clothing before reuse.

Wash hands before eating, drinking, or smoking.

# 7.2 CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES

Storage: Keep out of the reach of children. Keep container tightly closed.

Store at room temperature and keep containers closed when not in

Print Date: 28-Aug-14

use. Avoid any dust buildup by frequent cleaning and suitable

construction of the storage area. Keep dry until use.

# Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

# 8.1 CONTROL PARAMETER Exposure Guidelines

| Occupational Exposure Limits |                                      |                         |  |
|------------------------------|--------------------------------------|-------------------------|--|
| Chemical Name                | OSHA-PEL                             | ACGIH-TLV               |  |
| Crystalline Silica, Quartz   | 0.1 mg/m³                            | 0.025 mg/m <sup>3</sup> |  |
| Portland cement              | 5 mg/m³ (resp.)<br>15 mg/m³ (total)  | 10 mg/m³ (resp.)        |  |
| Gypsum                       | 10 mg/m³ (Resp.)<br>15 mg/m³ (Total) | 10 mg/m³                |  |
| Calcium Hydroxide            | 5 mg/m³ (Total)                      | 5 mg/m³                 |  |

## **8.2 EXPOSURE CONTROLS**

Engineering Controls: Use ventilation adequate to keep exposures (airborne levels of



dust, fume, vapor, etc.) below recommended exposure limits.

#### 8.3 INDIVIDUAL PROTECTION MEASURES

### 8.3a. Personal Protective Equipment:

- **i. Eye/Face Protection:** Wear approved eye protection [properly fitted dust- or splash-proof chemical safety goggles/face (face shield)]
- ii. Skin Protection:
  - 1. Hand Protection: Wear chemical resistant gloves.
  - 2. Body Protection: Wear suitable protective clothing
- iii. Respiratory Protection: A NIOSH approved dust mask or filtering face piece is recommended in poorly ventilated areas or when permissible exposure limits may be exceeded. Respirators should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134) and ANSI's standard for respiratory protection (Z88.2).
- iv. General Health and Safety Measures: Handle according to established industrial hygiene and safety practices.

# **Section 9: PHYSICAL AND CHEMICAL PROPERTIES**

| Appearance (physical state, color, etc.): | Solid Powder (Gray or White) |
|---|------------------------------|
| Odor:                                     | Characteristic               |
| Odor Threshold:                           | Not available                |
| pH:                                       | 10 – 12.5 when wet           |
| Melting point/Freezing point:             | Not available                |
| Initial boiling point and boiling range:  | Not available                |
| Flash point:                              | > 212°F                      |
| Evaporation rate (Water=1):               | Not available                |
| Flammability:                             | Not flammable                |
| Upper Flammability/Explosive Limit:       | Not available                |
| Lower Flammability/Explosive Limit:       | Not available                |
| Vapor Pressure                            | Not available                |
| Vapor Density:                            | Not available                |
| Relative Density:                         | 2 – 3 g/cc                   |
| Solubility in Water:                      | Slightly Soluble             |
| Partition coefficient: n-octanol/water:   | Not available                |
| Auto-ignition temperature:                | Not available                |
| Decomposition Temperature:                | Not available                |
| Viscosity (cps):                          | Not available                |
| VOC Content:                              | 0 g/L (0%)                   |



# Section 10: STABILITY AND REACTIVITY

#### 10.1. REACTIVITY

No dangerous reaction known under conditions of normal use.

## 10.2. CHEMICAL STABILITY

Stable under normal storage conditions. Keep dry in storage.

### 10.3. POSSIBILITY OF HAZARDOUS REACTION

No dangerous reaction known under conditions of normal use.

#### 10.4. CONDITIONS TO AVOID

Heat. Incompatible materials.

### 10.5. INCOMPATIBLE MATERIALS

Strong acids. Strong Oxidizers.

# 10.6. HAZARDOUS DECOMPOSITION PRODUCTS

Upon decomposition, this product may yield oxides of carbon and hydrogen sulfide.

# Section 11: TOXICOLOGICAL INFORMATION

### 11.1. LIKELY ROUTES OF EXPOSURE:

Skin contact, skin absorption, eye contact, inhalation, and ingestion.

#### 11.2. SYMPTOMS RELATED TO PHYSICAL/CHEMICAL/TOXICOLOGICAL CHARACTERISTICS:

Eye Contact: Causes serious eye damage. Symptoms may include discomfort or

pain, excess blinking and tear production, with marked redness and

swelling of the conjunctiva.

Skin Contact: Causes skin irritation. Handling can cause dry skin, discomfort,

irritation, and dermatitis.

Inhalation: May cause respiratory tract irritation. Causes damage to organs

through prolonged or repeated exposure. This product contains crystalline silica. Prolonged or repeated inhalation of respirable crystalline silica from this product can cause silicosis, a serious

Print Date: 28-Aug-14

disabling and fatal lung disease.

Ingestion: May be harmful if swallowed. Ingestion may cause discomfort

and/or distress, nausea or vomiting.

| Acute Toxicity             |               |               |
|----------------------------|---------------|---------------|
| Chemical Name              | LC50          | LD50          |
| Crystalline Silica, Quartz | Not available | Not available |



| Portland cement   | Not available | Not available         |
|-------------------|---------------|-----------------------|
| Gypsum            | Not available | Not available         |
| Calcium Hydroxide | Not available | Oral: 7340 mg/kg, rat |

| Carcinogenicity            |   |  |
|----------------------------|---|--|
| Chemical Name              | Chemical Listed as Carcinogens or<br>Potential Carcinogen<br>(NTP,IARC,OSHA,ACGIH,CP65) |  |
| Crystalline Silica, Quartz | N-A2, I-1, O-1, ACGIH-A2, CP65  |  |
| Portland cement            | ACGIH-A4  |  |
| Gypsum                     | Not Listed  |  |
| Calcium Hydroxide          | Not Listed  |  |

# 11.3. DELAYED, IMMEDIATE, AND CHRONIC EFFECTS OF SHORT AND LONG-TERM EXPOSURE

| SHORT-TERM                        |  |
|-----------------------------------|--|
| Skin Corrosion/Irritation:        | Causes skin irritation                       |
| Serious Eye Damage/Irritation:    | Causes severe eye damage                     |
| Respiratory Sensitization:        | Not available                                |
| Skin Sensitization:               | Not available                                |
| STOT-Single Exposure:             | May cause respiratory irritation             |
| Aspiration Hazard:                | Not available                                |
| LONG-TERM                         |  |
| Carcinogenicity:                  | May cause cancer                             |
| Germ Cell Mutagenicity:           | Not available                                |
| Reproductive Toxicity:            | Not available                                |
| STOT-Repeated Exposure:           | Causes damage to organs through prolonged or |
|                                   | repeated exposure                            |
| Synergistic/Antagonistic Effects: | Not available                                |

# **Section 12: ECOLOGICAL INFORMATION**

# 12.1. ECOTOXICITY

May cause long-term adverse effects to the aquatic environment. Keep from entry into sewers and waterways.

| Ecotoxicity                |                    |                    |
|----------------------------|--------------------|--------------------|
| Chemical Name              | EC50/NOEC-48 Hours | LC50/NOEC-96 Hours |
| Crystalline Silica, Quartz | Not available      | Not available      |
| Portland cement            | Not available      | Not available      |
| Gypsum                     | Not available      | Not available      |
| Calcium Hydroxide          | Not available      | Not available      |

# 12.2. PERSISTENCE AND DEGRADABILITY

Not available



## 12.3. BIOACCUMULATIVE POTENTIAL

Not available

### 12.4. MOBILITY IN SOIL

Not available

## 12.5. OTHER ADVERSE EFFECTS

Not available

# **Section 13: DISPOSAL CONSIDERATIONS**

#### 13.1. DISPOSAL METHOD

Dispose of contents/containers in accordance with all local, state, provincial, and federal regulations

### 13.2. OTHER DISPOSAL CONSIDERATIONS

Not available

# **Section 14: TRANSPORT INFORMATION**

| DOT (U.S.)                     | TDG (CANADA)                   |
|--------------------------------|--------------------------------|
| UN NUMBER:                     | UN NUMBER:                     |
|                                |                                |
| Not regulated                  | Not regulated                  |
| UN PROPER SHIPPING NAME:       | UN PROPER SHIPPING NAME:       |
| Not regulated                  | Not regulated                  |
| TRANSPORT HAZARD CLASS (ES):   | TRANSPORT HAZARD CLASS (ES):   |
|                                |                                |
| Not regulated                  | Not regulated                  |
| PACKING GROUP (if applicable): | PACKING GROUP (if applicable): |
|                                |                                |
| Not regulated                  | Not regulated                  |

SUMMARY: Product is NOT regulated under DOT/TDG and other transportation regulations.

### 14.1. ENVIRONMENTAL HAZARDS

Not available

# 14.2. TRANSPORT IN BULK ACCORDING TO ANNEX II OF MARPOL 73/78 AND THE IBC CODE Not available

# 14.3. SPECIAL PRECAUTIONS FOR USER

Do not handle until all safety precautions have been read and understood.



# **Section 15: REGULATORY INFORMATION**

# 15.1. SAFETY, HEALTH AND ENVIRONMENTAL REGULATIONS/LEGISLATIONS SPECIFIC FOR THE CHEMICAL

**Canada:** This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the SDS contains all the information required by the Controlled Products Regulations.

**US:** SDS prepared pursuant to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

### 15.2. US FEDERAL INFORMATION:

This product does not contain any hazards in accordance to the Superfund Amendments and Reauthorization Act of 1986 Title III (SARA Title III, Section 302/304/313)

## 15.3. US STATE RIGHT TO KNOW LAWS:

| California Proposition 65:               | <b>WARNING!</b> This product contains a chemical known to the State of California to cause cancer, birth defects or other reproductive harm         |
|--|---|
| Other U.S. States "Right to Know" Lists: |   |
| New Jersey:                              | Silica, quartz: CAS#14808-60-7 Silicate, Portland cement: CAS#65997-15-1 Gypsum (Calcium Sulfate): CAS#7778-18-9 Calcium Hydroxide: CAS#1305-62-0   |
| Pennsylvania:                            | Silica, quartz: CAS#14808-60-7 Silicate, Portland cement: CAS#65997-15-1 Gypsum (Calcium Sulfate): CAS#7778-18-9 Calcium Hydroxide: CAS#1305-62-0   |
| Massachusetts:                           | Silica, Crystalline, Quartz: CAS#14808-60-7 Portland Cement: CAS#65997-15-1 Gypsum: CAS#7778-18-9 Calcium Hydroxide: CAS#1305-62-0                  |
| Minnesota:                               | Silica, quartz: CAS#14808-60-7 Cement, Portland, Chemicals: CAS#65997-15-1 Gypsum (Calcium Sulfate): CAS#7778-18-9 Calcium Hydroxide: CAS#1305-62-0 |
| Florida:                                 | Not Available   |
| Michigan:                                | Not Available   |

# 15.4. GLOBAL INVENTORIES


| Chemical Name | USA TSCA | Canada   |
|---------------|----------|----------|
|               |          | DSL/NDSL |

Page 10 of 12





| Crystalline Silica, Quartz | Yes | DSL |
|----------------------------|-----|-----|
| Portland cement            | Yes | DSL |
| Gypsum                     | Yes | DSL |
| Calcium Hydroxide          | Yes | DSL |

#### 15.5. NFPA AND HMIS RATINGS:



| Hazard Index |                 |
|--------------|-----------------|
| 4            | Severe Hazard   |
| 3            | Serious Hazard  |
| 2            | Moderate Hazard |
| 1            | Slight Hazard   |







#### 15.6. SOURCE AGENCY CARCINOGEN CLASSIFICATIONS:

| CP65      | California Proposition 65   |  |
|-----------|---|--|
| OSHA (O)  | Occupational Safety and Health Administration   |  |
| ACGIH (G) | American Conference of Governmental Industrial Hygienists   |  |
|           | A1 – Confirmed human carcinogen   |  |
|           | A2 – Suspected human carcinogen   |  |
|           | A3 – Animal carcinogen  |  |
|           | <ul> <li>A4 – Not classifiable as a human carcinogen</li> </ul>   |  |
|           | <ul> <li>A5 – Not suspected a human carcinogen</li> </ul>   |  |
| IARC (I)  | International Agency for Research on Cancer   |  |
|           | <ul> <li>1 – The agent (mixture) is carcinogenic to humans</li> </ul>   |  |
|           | <ul> <li>2A – The agent (mixture) is probably carcinogenic to humans; there is limited evidence of carcinogenicity in humans and sufficient evidence of carcinogenicity in experimental animals.</li> <li>2B – The agent (mixture) is possibly carcinogenic to humans; there is limited evidence of carcinogenicity in humans in the absence of sufficient evidence of carcinogenicity in experimental animals.</li> <li>3 – The agent (mixture, exposure circumstance) is not classifiable as to its carcinogenicity to humans.</li> </ul> |  |
|           | <ul> <li>4 – The agent (mixture, exposure circumstance) is probably not<br/>carcinogenic to humans.</li> </ul>  |  |
| NTP (N)   | National Toxicology Program   |  |
|           | 1 – Known to be carcinogens   |  |
|           | 2 – Reasonably anticipated to be carcinogens  |  |

# **Section 16: OTHER INFORMATION**

**Date of Preparation:** August 28, 2014

Version: 2.0

Revision Date: N/A

**Disclaimer:** We believe the statements, technical information and recommendations contained are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.

Prepared by: Jamo

Phone: (562)-968-2980 www.jamoinc.com

# **End of Safety Data Sheet**