

# MULTI-PURPOSE FLEX THIN-SET MORTAR SUITABLE FOR BONDING TILE OVER USG LEVELROCK® BRAND FLOOR UNDERLAYMENT

Jamo® considers the LEVELROCK® Brand Floor Underlayment, as manufactured by US Gypsum (USG), and installed by USG licensed LEVELROCK Applicators in accordance with their directions, a suitable underlayment for the installation of ceramic tile with Jamo's Multi-Purpose Flex Thin-Set Mortar. LEVELROCK underlayments and radiant floor heating systems are being specified in multi-level condominiums, hotels and high-rise office buildings in conjunction with ceramic tile and dimensional stone installations.

Tile and dimensional stone can be installed over LEVELROCK Brand in areas designated as interior, dry, and above grade floors for residential and commercial traffic. Once the LEVELROCK Brand is properly installed and cured in accordance with the manufacturer's directions, preparation for the installation of ceramic tile may begin.

## STEP 1

LEVELROCK Brand Underlayments must be installed by a USG licensed applicator according to US Gypsum requirements.

## STEP 2

LEVELROCK Brand Underlayments must be cured, dry, free of all contaminants and all cracks and defects repaired per USG specifications.

## STEP 3

All LEVELROCK Brand Underlayments to receive tile must be sealed with USG Sealer per US Gypsum requirements.

## STEP 4

Install tile with Jamo's Multi-Purpose Flex Thin-Set Mortar according to ANSI A108.5 specifications.

## STEP 5

Grout with Jamo's Master Color™ according to ANSI A108.10 specifications.

## WARRANTY SYSTEM

Jamo has given this tile installation system utilizing Multi-Purpose Flex Thin-Set Mortar and Master Color grout a 10 year warranty. An additional 5 year warranty can be obtained by applying Jamo's Waterproof Waterproofing Membrane prior to STEP 4.

This warranty is subject to the terms and conditions of the Installations Systems Warranty.

Please contact Architectural Services for further system or warranty details.

The warranty and performance of LEVELROCK Brand Floor Underlayment is the responsibility of US Gypsum Company, and not that of Jamo.

The information in this bulletin is presented in good faith, but no warranty, express or implied, is given nor is freedom from any patent in as much as any assistance furnished by Jamo with reference to the safe use and disposal of its products provided without charge. Jamo assumes no obligation or liability therefore, except to the extent that any such assistance shall be given in good faith.

TB3A

